

Electric Scissor Lifts **OPTIMUM 8**

TECHNICAL DATA

Working height	7.77 m
Platform height	5.77 m
Platform length	1.72 m
Platform length - extended	2.59 m
Length - extension	0.86 m
Platform width - outside	0.74 m
Height - stowed	1.98 m
Overall width	0.79 m
Length	1.9 m
Wheelbase	1.38 m
Ground clearance - center	8.7 cm
Ground clearance - deployed potholes	2 cm
Drive speed	0.5 - 4.5 km/h
Max. drive working height	5.77 m
Gradeability	25 %
Tilt	1.5° / 3°
Turning radius - outside	1.5 m
Non-marking tyres	12.5 x 4.13
Batteries	24 V - 225 Ah

Hydraulic system capacity	7 l
Weight	1 590 kg
Platform size - extended	2.59 x 0.74 m
Lift capacity - inside	230 kg (2 pers.)
Lift capacity - outside	230 kg (1 pers.)
Lift capacity on the extension	230 kg
Length - extension XL option	0 m

STANDARD EQUIPMENT

- Proportional controls
- 24 V electric drive brushless AC motors
- Battery level indicator on upper and lower control boxes
- Haulotte Activ'Screen (battery charge, Hourmeter, service alert & failures icons in code or in full text...)
- 2 swing out trays
- Lateral fork lifting pockets
- Electric or manual break release system
- Lifting and stowage points
- Non marking tyres
- Pothole guards
- Tilt sensor
- 2 front steering and 2 rear driving wheels
- Haulotte Activ'Energy Management: Smart CAN charger

MAIN OPTIONS

- Pipe cradle
- Panel carrier
- Flashing light
- Dual flashing lights
- Working light
- AC power to platform
- Hydraulic oil for cold countries
- Folding guardrails
- Telematics ready