

# Electric Scissor Lifts COMPACT 10N

## MAIN OPTIONS

- Flashing light
- Travel alarm
- Working light
- Power to platform
- Biodegradable hydraulic oil
- Folding guardrails (C 8)
- Centralised battery filling
- Telematics ready

## TECHNICAL DATA

Working height	10 m
Platform height	8 m
Platform length	2.31 m
Platform length - extended	3.23 m
Length - extension	0.92 m
Platform width - outside	0.81 m
Storage height	1.32 m
Height - stowed	2.18 m
Overall width	0.81 m
Length	2.49 m
Wheelbase	1.86 m
Ground clearance - center	13 cm
Ground clearance - deployed potholes	2.5 cm
Drive speed	1 - 3.2 km/h
Max. drive working height	8 m
Gradeability	23 %
Tilt	2 °
Turning radius - outside	2.38 m
Non-marking tyres	15 x 5
Batteries	24 V - 225 Ah (C20)
Hydraulic system capacity	27 l
Weight	2 190 kg
Platform size - extended	3.23 x 0.81 m
Lift capacity - inside	230 kg (2 pers.)
Lift capacity - outside	N/A
Lift capacity on the extension	120 kg
XL platform length (option)	0 m
XL platform length - extended (option)	0 m
Length - extension XL option	0 m

## STANDARD EQUIPMENT

- Pothole guards
- Battery charge indicator
- Proportional lift and drive
- Folding handrails (C 10N)
- Swing out component tray
- Battery charger with automatic stop
- Solid non-marking tyres
- Free wheeling device
- Tilt controller
- Load Management System in the platform
- Manual platform lowering valve
- Integrated forklift pockets
- Towing hooks
- Horn
- Hourmeter
- Removable control box in platform
- 24 V DC motor
- 2 front steering & driving wheels