

# Electric Scissor Lifts COMPACT 12

## MAIN OPTIONS

- Flashing light
- Travel alarm
- Working light
- Power to platform
- Biodegradable hydraulic oil
- Folding guardrails
- Maintenance-free batteries
- Traction batteries
- Centralised battery filling

## TECHNICAL DATA

Working height	11.98 m
Platform height	9.98 m
Platform length	2.31 m
Platform length - extended	3.23 m
Length - extension	0.92 m
Platform width - outside	1.2 m
Storage height	1.53 m
Height - stowed	2.39 m
Overall width	1.2 m
Length	2.49 m
Wheelbase	1.86 m
Ground clearance - center	13 cm
Ground clearance - deployed potholes	2.5 cm
Drive speed	0.8 - 2.9 km/h
Max. drive working height	9.98 m
Gradeability	23 %
Tilt	2 °
Turning radius - outside	2.5 m
Non-marking tyres	15 x 5
Batteries	24 V - 340 Ah (C 20)
Hydraulic system capacity	27 l
Weight	2 470 kg
Platform size - extended	3.23 x 1.2 m
Lift capacity - inside	300 kg (2 pers.)
Lift capacity - outside	300 kg (1 pers.)
Lift capacity on the extension	150 kg
Length - extension XL option	0 m

## STANDARD EQUIPMENT

- 24 V DC motor
- Pothole guards
- Battery charge indicator
- Proportional lift and drive
- Removable control box in platform
- Swing out component tray
- Battery charger with automatic stop
- Solid non-marking tyres
- Free wheeling device
- Tilt controller
- Load Management System in the platform
- Manual platform lowering valve
- Integrated forklift pockets
- Towing hooks
- Horn
- Hourmeter
- 2 front steering & driving wheels