

Electric Scissor Lifts **COMPACT 14**

MAIN OPTIONS

- Flashing light
- Working light
- Power to platform
- Biodegradable hydraulic oil
- Centralised battery filling
- Swing door entry gate
- Pipe cradle

TECHNICAL DATA

Working height	13.85 m
Platform height	11.85 m
Platform length	2.31 m
Platform length - extended	3.23 m
Length - extension	0.92 m
Platform width - outside	1.2 m
Storage height	2.08 m
Height - stowed	2.5 m
Overall width	1.2 m
Length	2.49 m
Wheelbase	1.86 m
Ground clearance - center	13 cm
Ground clearance - deployed potholes	2.3 cm
Drive speed	0.9 - 2.7 km/h
Max. drive working height	11.85 m
Gradeability	23 %
Tilt	2° / 3°
Turning radius - outside	2.5 m
Non-marking tyres	15 x 5
Batteries	24 V - 330 Ah (C20)
Hydraulic system capacity	25 l
Weight	3 175 kg
Platform size - extended	3.23 x 1.2 m
Lift capacity - inside	350 kg (3 pers.)
Lift capacity on the extension	150 kg
Length - extension XL option	0 m

STANDARD EQUIPMENT

- Pothole guards
- Battery charge indicator
- Proportional lift and drive
- Removable control box in platform
- Swing out component tray
- Battery charger with automatic stop
- Solid non-marking tyres
- Brake release
- Tilt controller
- Load Management System in the platform
- Manual platform lowering valve
- Integrated forklift pockets
- Towing hooks
- Horn
- Hourmeter
- Folding handrails
- 2 front steering & driving wheels
- 24 V DC motor